

DP Big Whole House Taste, Odor, and Scale Reduction Trio System

Designed for high flow point of entry applications to provide clean, clear drinking water and protect pipes, appliances, and fixtures

Atlas Filtri® DP Big Sediment, Taste, Odor, and Scale Reduction unit is a point-of-entry, water filtration system for the whole house. Designed to reduce sediment, taste, color, odor and lime scale build up in high flow whole house applications.

The first stage of the PET housing accepts a 5-micron, 20" sediment filter that includes a special grade of polyphosphate media to reduce scale build up on pipes, dish washers, fixtures, washing machine, and tankless and heating tank systems.

The second and third stages accept a 5-micron, 20" carbon block made from coconut shell carbon. Reduces taste, odor and clarity of the water, providing bottle-quality water. The wall mounted filtration unit is designed to be installed at the entry point of a house to accommodate flow rates of up to 20 gallons per minute. Designed to handle a maximum pressure of 120psi @ 113°F (45°C) maximum temperature. Standard inlet and outlet connections are 1" NPT. Standard head unit is reinforced polypropylene and sump is PET. Standard O-ring is EPDM.

The melt-blown BIG smooth cartridge and carbon block come in a 20" length and are made to comply with the most stringent regulations for applications of drinking water. These five (5) micron polypropylene cartridges are suitable for many filtration applications due to the wide chemical-physical compatibility for a variety of water-based solutions.

The polyphosphate incorporated into the center core of the filter is designed to slowly release. It is a low acid media specifically designed for extreme water conditions found in high temperature filtration applications. The media will last up to 12 months on typical water supplies up to 15 grains hard

Atlas Filtri is driven to providing our customer with the best available products to meet specific filtration requirements. This is done by using the most advanced manufacturing and design methods. The international patents received come from a constant commitment to research and develop that result in new and innovative products.

Learn more at us.atlasfiltri.com.

Specifications

- Designed for high flow residential filtration applications
- Accommodates (3) single standard 4.5"
 OD filter cartridges
- 1" NPT inlet and outlet fitting connections

Features

- Includes pressure-relief feature that includes an O-ring seal. No spring is used that can result in water leaks due to corrosion
- Knife-edge flat washer at both cartridge ends create a positive and seal eliminating by-pass
- Works with standard double open-end cartridges with scale reduction media included

Materials:

Head Connection: reinforced polypropylene Housing Construction: PET

Seal: FDA Grade EPDM

Filter construction: polypropylene and coconut

shell carbon media

Filter media: Glassy polyphosphate

Working Conditions:

Working Temperature Range: Min 39.2°F (4°C) – Max 113°F (45°C)

Media temperature range of dissolved polyphosphate: Max 220°F (104°C) in heated environment

All components sold separately







DP Big Trio Plastic Housing Metal Powder Coated White Bracket Filter Wrench Lubricant

5 Micron Scale Reduction Filter 5 Micron Carbon Block Filter (QTY 2)




NSF/ANSI Test and Approved IAPMO Certification

PRODUCT SPECIFICATION and PERFORMANCE


Listed DP BIG housing models with sediment and scale reduction cartridges

Model	Description	Size	Fitting	Box QTY		Box Size	9	Weight
ZC1803737	DP BIG PS PM 20 Trio 1" NPT IN	20"	1"	1	18	3" 24"	8.5"	17.30lb
	AB DP Big Trio Wall Bracket							
	Drain Kit DP BIG (QTY 3)		1/2"					
	Gauge DP BIG (QTY 4)		1/8"					
Model	Description	Size	Micron					
			Rating	Box QTY	E	Box Size	Weight	
RA5777608	CPP-SP 20 Big SX 5 micron Sediment/Scale filter	4.5"x 20"	5	6	21.2"	9.8"	14.7"	14.24lb
RE4520CT5	CB-AF Big CTO 20 SX 5 mcr	4.5" x 20"	5	6	17.2"	12.5".	21.5".	42lb



Removal Efficiency in %

Removal Efficiency In (%) Percentage



Atlas Filtri® is a registered trade mark of ATLAS FILTRI srl. Unauthorized use of the registered trade mark is prohibited. Images and context are the property of ATLAS FILTRI srl, which reserves the right to change product design and specification without prior notification.



1068 North Farms Road, Building 3, Wallingford, CT 06492, USA Office +1 (203) 284-0080 - Fax +1 (203) 294-9226 – email: atlasfiltrinorthamerica@atlasfiltri.com A Company of the Atlas Filtri Group. World headquarters and production facilities located in Italy.

